

[键入文字]



HiOSO Technology Co., Ltd.

HiOSO FOWAY Series Switches

| | |
|---|----------|
| FOWAY1309FC 100M/1000M Fiber Switch..... | 2 |
| FOWAY1509FC 1000M Fiber Switch..... | 4 |
| FOWAY3000-18FSC 100M/1000M Fiber Switch..... | 6 |
| FOWAY3000-26FSC 100M/1000M Fiber Switch..... | 8 |

Website: www.hioso.com www.haishuo.com
Tel: 0086 755 83128820 Fax: 0086 755 83151488
Email: market@hioso.com
Address: 6TH Flr, 12th Bld, Wangtang Industrial Zone, Xingao Rd, Xili, Nanshan District, Shenzhen

[键入文字]



HiOSO Technology Co., Ltd.

FOWAY1309FC 100M/1000M Fiber Switch



Overview

HiOSO FOWAY1309FC is a nine ports 100M all optic fiber switch. It offers 8 100M SFP fiber ports access and 1 Gigabit Combo port (1000M SFP port or 10/100/1000M adaptive RJ45 Ethernet optional) uplink.

FOWAY1309FC supports SFP modules hot plug, and supports to work with fiber switches, fiber converters and other devices with fiber ports. It supports WEB management and SNMP management; applies to security system, electric system, traffic system requirements.

Character

- ℓ Support maximum 8 SFP fiber ports and 1 GE Combo port (SFP fiber port/RJ45 port interchange)
- ℓ Support SFP hot plug
- ℓ Support each port full rate, full-duplex non-blocking forwarding
- ℓ Support 8K MAC learning, 1Mbit storage and forward cache space, 4.6G back plane bandwidth
- ℓ Supports to substitute central fiber converter, simplify network structure, lower network establishing cost, reduce device fault
- ℓ All optic ports, strengthen the an-interference ability
- ℓ Metal casing design, better for heat dissipation

Website: www.hioso.com www.haishuo.com

Tel: 0086 755 83128820 Fax: 0086 755 83151488

Email: market@hioso.com

Address: 6TH Flr,12th Bld,Wangtang Industrial Zone,Xingao Rd,Xili,Nanshan District,Shenzhen

[键入文字]



HiOSO Technology Co., Ltd.

Technical Specification

| Parameter | Specification |
|---------------------|---|
| Standard | IEEE802.3 10Base-T Ethernet, IEEE802.3u 100Base-TX/FX Fast Ethernet, IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-SX/LX Gigabit Ethernet, IEEE802.1d Spanning Tree |
| Wavelength | 850nm/1310nm/1550nm |
| Distance | 100M SFP multi-mode: 2Km Single-mode: 20/40/60/80/100/120Km Single-fiber single-mode: 25/40/60/80/100/120Km 1000M SFP multi-mode: 220m (fiber 62.5/125 μ m) / 550m (fiber 50/125 μ m) Single-mode: 10/20/40/60/80/100/120Km Single-fiber single-mode: 10/20/40/60/80/100/120Km Cat5: 100m |
| Port | 8 100M SFP fiber ports: 100Mbps 1 Gigabit Combo port: 1 Gbps, 1000M SFP&10/100/1000M RJ45 |
| MAC | 8K |
| Buffer memory space | 1Mbit |
| Bit error rate | <1/1000000000 |
| MTBF | 100000 hours |
| Power | DC12V/2A |
| Power consumption | 10W |
| Working temperature | -10~60 $^{\circ}$ C |
| Storage temperature | -40~80 $^{\circ}$ C |
| Humidity | 5%~90% non-condensing |
| Dimension | 28mm (H) \times 193mm (W) \times 119mm (D) |

Website: www.hioso.com www.haishuo.com

Tel: 0086 755 83128820 Fax: 0086 755 83151488

Email: market@hioso.com

Address: 6TH Flr, 12th Bld, Wangtang Industrial Zone, Xingao Rd, Xili, Nanshan District, Shenzhen

FOWAY1509FC 1000M Fiber Switch



Overview

HiOSO FOWAY1509FC is a nine ports Gigabit fiber switch, with 8 1000M SFP fiber ports and 1 1000M Combo port (100M / 1000M SFP port or 10/100/1000M RJ45 port optional) uplink.

FOWAY1509FC supports SFP modules hot plug, and supports to work with fiber switches, fiber converters and other devices with fiber ports. It supports WEB management and SNMP management; applies to security system, electric system, traffic system requirements.

Character

- ℓ Support 8 Gigabit SFP access and 1 Gigabit Combo port (100M or 1000M SFP optional, or 10/100/1000M RJ45 port)
- ℓ Support SFP hot plug
- ℓ Support full rate, full-duplex non-blocking forwarding at each port
- ℓ Support 8K MAC learning, 1Mbit storage and forward cache space, 18G back plane bandwidth
- ℓ Supports to substitute central fiber converter, simplify network structure, lower network establishing cost, reduce device fault
- ℓ All optic ports, strengthen the an-interference ability
- ℓ Metal casing design, better for heat dissipation

Website: www.hioso.com www.haishuo.com

Tel: 0086 755 83128820 Fax: 0086 755 83151488

Email: market@hioso.com

Address: 6TH Flr, 12th Bld, Wangtang Industrial Zone, Xingao Rd, Xili, Nanshan District, Shenzhen

Technical Specification

| | |
|---------------------|---|
| Parameter | Specification |
| Standard | IEEE802.3 10Base-T Ethernet, IEEE802.3u 100Base-TX/FX Fast Ethernet, IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-SX/LX Gigabit Ethernet, IEEE802.1d Spanning Tree |
| Wavelength | SFP:850nm/1310nm/1490nm/1550nm |
| Distance | 100M SFP Multi-mode: 2km (fiber size 62.5/125 μ m or 50/125 μ m) Single-mode: 20/40/60/80/100/120Km Single-fiber single-mode: 25/40/60/80/100/120Km 1000M SFP Multi-mode: 220m (fiber size 62.5/125 μ m) / 550m (fiber size 50/125 μ m) Single-mode: 10/20/40/60/80/100/120Km Single-fiber single-mode: 10/20/40/60/80/100/120Km CAT5: 100m |
| Port | 8 Gigabit SFP fiber ports: 1000Mbps 1 Gigabit Combo port:: 1 Gbps, 100M/1000M SFP&10/100/1000M RJ45 |
| MAC | 8K |
| Buffer memory space | 1Mbit |
| Bit error rate | <1/1000000000 |
| MTBF | 100000 hours |
| Power | DC12V/2A |
| Power consumption | 10W |
| Working temperature | -10~60 $^{\circ}$ C |
| Storage temperature | -40~80 $^{\circ}$ C |
| Humidity | 5%~90% non-condensing |
| Dimension | 28mm (H) \times 193mm(W) \times 119mm (D) |

Order information

| No | Type | Managed | Ports |
|----|--------------|---------|---|
| 1 | FOWAY1509FC | Not | 8 1000Base-FX SFP ports + 1 Gigabit Combo uplink (SFP fiber port /RJ45 Ethernet port optional) |
| 2 | FOWAY1509FCM | Support | 8 1000Base-FX SFP ports + 1Gigabit Combo uplink ((SFP fiber port /RJ45 Ethernet port optional) |

Website: www.hioso.com www.haishuo.com

Tel: 0086 755 83128820 Fax: 0086 755 83151488

Email: market@hioso.comAddress: 6TH Flr, 12th Bld, Wangtang Industrial Zone, Xingao Rd, Xili, Nanshan District, Shenzhen

FOWAY3000-18FSC 100M/1000M Fiber Switch

Overview

HiOSO FOWAY3000-18FSC is a 18 ports 100M and1000M hybrid all optic fiber switch. It offers 16 100M SFP fiber ports access and 2 Gigabit Combo port (100/1000M SFP port or 10/100/1000M adaptive RJ45 Ethernet optional) uplink.

FOWAY3000-18FSC supports SFP modules hot plug, and supports to work with fiber switches, fiber converters and other devices with fiber ports. It supports WEB management and SNMP management; applies to security system, electric system, traffic system requirements.



Character

- ℓ Support maximum 16 SFP fiber ports and 2 GE Combo port (SFP fiber port/RJ45 port interchange)
- ℓ Support SFP hot plug
- ℓ Support each port full rate, full-duplex non-blocking forwarding
- ℓ Support 8K MAC learning, 2Mbit storage and forward cache space, 7.2G back plane bandwidth
- ℓ Supports to substitute central fiber converter, simplify network structure, lower network establishing cost, reduce device fault
- ℓ All optic ports, strengthen the an-interference ability
- ℓ Metal casing design, better for heat dissipation, supports 1U rack installation

Website: www.hioso.com www.haishuo.com

Tel: 0086 755 83128820 Fax: 0086 755 83151488

Email: market@hioso.com

Address: 6TH Flr,12th Bld,Wangtang Industrial Zone,Xingao Rd,Xili,Nanshan District,Shenzhen

[键入文字]



HiOSO Technology Co., Ltd.

Technical Specification

| | |
|---------------------|---|
| Parameter | Specification |
| Standard | IEEE802.3 10Base-T Ethernet, IEEE802.3u 100Base-TX/FX Fast Ethernet, IEEE802.3ab 1000Base-T Ethernet, IEEE802.3z 1000Base-SX/LX Gigabit Ethernet, IEEE802.1d Spanning Tree, IEEE802.1w Rapid Spanning Tree, IEEE802.1s Multiple Spanning Tree, IEEE802.1q VLAN, IEEE802.1p QoS |
| Wavelength | SFP module: 850nm/1310nm/1550nm |
| Distance | 100M SFP multi-mode: 2Km Single-mode: 20/40/60/80/100/120Km Single-fiber single-mode: 25/40/60/80/100/120Km 1000M SFP multi-mode: 220m (fiber 62.5/125μm) / 550m (fiber 50/125μm) Single-mode: 10/20/40/60/80/100/120Km Single-fiber single-mode: 10/20/40/60/80/100/120Km Cat5: 100m |
| Port | 16 100M SFP fiber ports: 100Mbps 2 Gigabit Combo ports: 1 Gbps, 100/1000M SFP & 10/100/1000M RJ45 |
| MAC | 8K |
| Buffer memory space | 2Mbit |
| Bit error rate | <1/1000000000 |
| MTBF | 100000 hours |
| Power | AC100~240V 50/60HZ |
| Power consumption | 20W |
| Working temperature | -10~60°C |
| Storage temperature | -40~80°C |
| Humidity | 5%~90% non-condensing |
| Dimension | 44mm (H) × 277mm (W) × 190mm (D) |

Order Information

| Type | Management | Ports |
|------------------|------------|--|
| FOWAY3000-18FSC | NO | 16 100M SFP ports + 2 Gigabit Combo uplink ports |
| FOWAY3000-18FSCM | YES | 16 100M SFP ports + 2 Gigabit Combo uplink ports |

Website: www.hioso.com www.haishuo.com

Tel: 0086 755 83128820 Fax: 0086 755 83151488

Email: market@hioso.com

Address: 6TH Flr, 12th Bld, Wangtang Industrial Zone, Xingao Rd, Xili, Nanshan District, Shenzhen

FOWAY3000-26FSC 100M/1000M Fiber Switch

Overview

HiOSO FOWAY3000-26FSC is a 26 ports 100M and 1000M hybrid all optic fiber switch. It offers 24 100M SFP fiber ports access and 2 Gigabit Combo port (100/1000M SFP port or 10/100/1000M adaptive RJ45 Ethernet optional) uplink.

FOWAY3000-26FSC supports SFP modules hot plug, and supports to work with fiber switches, fiber converters and other devices with fiber ports. It supports WEB management and SNMP management; applies to security system, electric system, traffic system requirements. It supports dual power hot backup and DC12V/5A power supply.



Character

- ℓ Support maximum 24 SFP fiber ports and 2 GE Combo port (SFP fiber port/RJ45 port interchange)
- ℓ Support SFP hot plug
- ℓ Support each port full rate, full-duplex non-blocking forwarding
- ℓ Support 8K MAC learning, 3Mbit storage and forward cache space, 8.8G back plane bandwidth
- ℓ Supports to substitute central fiber converter, simplify network structure, lower network establishing cost, reduce device fault
- ℓ Replace Media Converter in machine room side, simple network structure, reduce network system total cost and reduce device faults
- ℓ All optic ports, strengthen the anti-interference ability
- ℓ 1U rack type, supports max 3 pieces power supply hot backup (2 piece inside power supply AC100V~240V input access and 1 piece DC12V output access)
- ℓ DC12V/5V input port supports car battery access to ensure network working when the public power supply system is black out

Website: www.hioso.com www.haishuo.com

Tel: 0086 755 83128820 Fax: 0086 755 83151488

Email: market@hioso.com

Address: 6TH Flr, 12th Bld, Wangtang Industrial Zone, Xingao Rd, Xili, Nanshan District, Shenzhen

[键入文字]



HiOSO Technology Co., Ltd.

Technical Specification

| | |
|---------------------|---|
| Parameter | Specification |
| Standard | IEEE802.3 10Base-T Ethernet, IEEE802.3u 100Base-TX/FX Fast Ethernet, IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-SX/LX Gigabit Ethernet, IEEE802.1d Spanning Tree, IEEE802.1w Rapid Spanning Tree, IEEE802.1s Multiple Spanning Tree, IEEE802.1q VLAN, IEEE802.1p QoS |
| Wavelength | SFP module: 850nm/1310nm/1550nm |
| Distance | 100M SFP multi-mode: 2Km Single-mode: 20/40/60/80/100/120Km Single-fiber single-mode: 25/40/60/80/100/120Km 1000M SFP multi-mode: 220m (fiber 62.5/125μm) / 550m (fiber 50/125μm) Single-mode: 10/20/40/60/80/100/120Km Single-fiber single-mode: 10/20/40/60/80/100/120Km Cat5: 100m |
| Port | 24 100M SFP fiber ports: 100Mbps 2 Gigabit Combo ports: 1 Gbps, 100/1000M SFP & 10/100/1000M RJ45 |
| MAC | 8K |
| Buffer memory space | 3Mbit |
| Bit error rate | <1/1000000000 |
| MTBF | 100000 hours |
| Power | AC 100~240V 50/60HZ, DC 12V/5A |
| Power consumption | 50W |
| Working temperature | -10~60°C |
| Storage temperature | -40~80°C |
| Humidity | 5%~90% non-condensing |
| Dimension | 44mm (H) × 440mm (W) × 210mm (D) |

Order Information

| NO | Type | Management | Ports | Power Supply |
|----|---------------------|------------|--|----------------------------|
| 1 | FOWAY3000-26FSC | NO | 24 100M SFP ports + 2 Gigabit Combo uplink ports | Inside single power supply |
| 2 | FOWAY3000-26FSC-BP | NO | 24 100M SFP ports + 2 Gigabit Combo uplink ports | Inside dual power supply |
| 3 | FOWAY3000-26FSCM | YES | 24 100M SFP ports + 2 Gigabit Combo uplink ports | Inside single power supply |
| 4 | FOWAY3000-26FSCM-BP | YES | 24 100M SFP ports + 2 Gigabit Combo uplink ports | Inside dual power supply |

Website: www.hioso.com www.haishuo.com
 Tel: 0086 755 83128820 Fax: 0086 755 83151488
 Email: market@hioso.com
 Address: 6TH Flr, 12th Bld, Wangtang Industrial Zone, Xingao Rd, Xili, Nanshan District, Shenzhen